

feature radiators

effective from 1st February 2009



4 section dark olive brown shown above

BURLINGTON

create the elegance of a bygone era
with this cast iron radiator

BURLINGTON

838mm high
214mm deep

sections	length (mm)
3	252
4	328
5	404
6	480
7	556
8	632
9	708
10	784
11	860
12	936
13	1012
14	1088
15	1164
16*	1240
17*	1316
18*	1392
19*	1468
20*	1544
21*	1620
22*	1696
23*	1772
24*	1848

output		dark olive brown	other finishes
watts	btus	£	£
516	1760	342	371
689	2351	444	482
863	2945	546	594
1035	3531	648	706
1207	4118	750	818
1380	4709	853	929
1552	5295	955	1041
1724	5882	1057	1153
1892	6455	1159	1264
2069	7059	1261	1376
2236	7628	1363	1488
2408	8215	1465	1600
2587	8827	1568	1711
2753	9388	1670	1823
2925	9974	1772	1935
3097	10561	1874	2047
3269	11153	1976	2158
3441	11739	2078	2270
3613	12326	2180	2382
3784	12912	2288	2499
3956	13499	2390	2611
4128	14086	2492	2722

* Joining tool required for on site assembly. A joining tool with instructions can be supplied for £100 refundable deposit

- **Finishes**
- Available in *mat metallic finishes* (antique gold, light old penny, dark old penny, natural cast iron, anthracite, pewter) and a selection of *semi-gloss finishes* (some RAL colours, gun metal and black). Colour cards available on request.
- Shade variations may occur from one paint batch to the next and over the years our standard for some colours (including anthracite) has changed. Accordingly, where radiators are to be used in the same room and/or a colour match is important, it is advisable to order all radiators at the same time. If you are looking to match the colour of radiators ordered previously, please disclose this at the time of order, so we can do what we can to minimize the variation in shade.
- Warning: please be aware that pewter, white, cream and other light coloured paint finishes highlight the imperfections characteristic of cast iron more than the darker colours.
- Primer finish available for on site painting or we can deliver direct to your own painter in the UK. We strongly advise against powder coating this product as this process can weaken the seals between sections. Powder coating will invalidate the manufacturer's guarantee.
- These radiators have a textured finish which is characteristic of cast iron. If you are looking for a column style radiator with a smooth finish please see our Classic and Bordo ranges, which are made of steel.

▪ Further notes overleaf

www.featureradiators.com

bingley railway station, wellington street, bingley, west yorkshire bd16 2nb

tel. 01274 567789 fax. 01274 561183

email: contactus@featureradiators.com

feature radiators

- Lead times - dark olive brown: allow 10 – 15 working days / other finishes: please allow 5 weeks
- Delivery - nationwide - usually £25 per consignment
- Manufacturer's guarantee - 10 year manufacturer's guarantee against manufacturing defects – maximum working pressure of 6 bar
- Ready assembled - up to 15 sections can be delivered to site ready assembled. * for larger sizes a joining tool is required.
- Other sizes available – shown above are the most popular sizes. Other sizes available. For longer sizes further sections may be assembled on site – each section is 76mm wide, end bushes = 24mm
- Fixings - radiators are supplied with the necessary fixings i.e. wall bracket, plugs, bushes, vents, ½" connections as standard (¾" connections available on request) - note: screws are not supplied
- Valves - to complete the look see our valves page for traditional style valves (valves are not included as standard)
- Heat outputs are shown at operating temperatures of 90/70/20 ($\Delta t60^{\circ}\text{C}$)
- Pipe centre measurements
- Wall to pipe centre measurements: 125mm or 135mm - the standard bracket supplied has a choice of 2 settings. Use the greater wall to pipe centre measurement to accommodate skirting boards. Adjustable bracket available on request.
- Tapping centres = length of radiator
- Pipe centre to pipe centre = tapping centres (width of radiator) plus appropriate amount for valves
 - Using our valves (other than minimus valves):
Pipe centres = Tapping Centres plus 100mm
 - Using our minimus valves:
Pipe centres = Tapping Centres plus 86mm
 - Using other valves:
Your installer will be able to work out the pipe centres from the information provided.
- Water treatment – the manufacturer's guarantee will only be valid if your radiators are installed in accordance BS 5449 section five commissioning. On completion of installation the system should be properly flushed and filled to remove debris and minimise the presence of solid particles and chemical residues, which may cause corrosion and damage within the system. Use of the corrosion inhibitor should be in accordance with the manufacturer's instructions and recommendations and should take into account the particular metals within the system all
- All sales are subject to our standard terms and conditions a copy of which is available on request

the above prices are exclusive of VAT

www.featureradiators.com

bingley railway station, wellington street, bingley, west yorkshire bd16 2nb

tel. 01274 567789 fax. 01274 561183

email: contactus@featureradiators.com